

Product Catalog 2020

RackLine

AT&T Rack & Enclosure
LAN Cabling Products

AT&T Cabling Systems



AT&T Cabling Systems

Part D

RackLine™

AT&T Rack & Enclosure LAN Cabling Products

RackLine Server Cabinets.....	316
RackLine Network Cabinets.....	317-318
RackLine Wall Mount Network Cabinets.....	319
RackLine Wall Mount SOHO Network Cabinets	320
RackLine Cabinet Accessories.....	321-330
RackLine Basic Power Distribution Units	331

AT&T RackLine

Free Standing Server Cabinets

Description

Free standing 19" server cabinets	
Construction material	Sheet Steel
Size options	26U, 42U and 47U (other sizes available)
Width and depth options	600x1000mm or 800x1000mm
Color	Black RAL 9005
Accessories	Page D.5.1

Standard & EU Directives Conformance

- Mechanical structure conforming to EN 61587-1, IEC 60917 & IEC 60297
- Vibration & shock tests according to IEC 60068-2
- Corrosion resistance (salt spray) acc. to ISO 9227, ASTM B117
- IP20 according to IEC 60529
- Bonding & ground continuity according to IEC 61010-1
- EU Directive 2011/65/EU (RoHS-2)

Mechanical Properties

Static load capacity	1000 kg max.
Dynamic load capacity	750 kg max.
Front door	Detachable, single, 82% perforated
Rear door	Detachable, double, 82% perforated
Side panels	Detachable, key-locked
Profiles	U marking on both sides
Mounting	Normal floor or raised floor Optional raised floor fixing kit
Electrical grounding	Internal parts and frame grounding kit
Cabinet row formation	Aligning baying kit
Locking options	Standard: Mechanical lock Optional: Electronic key-access



Ordering Information

Description	Size	Dimensions mm	Color	P/N
Free standing 19" Server Cabinet	26U	600x1000	Black	7116100026A-BK51
Free standing 19" Server Cabinet	42U	600x1000	Black	7116100042A-BK51
Free standing 19" Server Cabinet	47U	600x1000	Black	7116100047A-BK51
Free standing 19" Server Cabinet	42U	800x1000	Black	7118100042A-BK51
Free standing 19" Server Cabinet	47U	800x1000	Black	7118100047A-BK51
Free standing 19" Server Cabinet	26U	600x1000	Gray	7116100026A-GY51
Free standing 19" Server Cabinet	42U	600x1000	Gray	7116100042A-GY51
Free standing 19" Server Cabinet	47U	600x1000	Gray	7116100047A-GY51
Free standing 19" Server Cabinet	42U	800x1000	Gray	7118100042A-GY51
Free standing 19" Server Cabinet	47U	800x1000	Gray	7118100047A-GY51

AT&T RackLine

Free Standing Network Cabinets

Description

Free standing 19" network cabinets	
Construction material	Sheet Steel
Size options	26U, 36U, 42U and 47U (other sizes available)
Width and depth options	600x800mm, 600x1000mm, 800x800mm or 800x1000mm
Color	Black RAL 9005
Accessories	Page D.5.2

Standard & EU Directives Conformance

- Mechanical structure conforming to EN 61587-1, IEC 60917 & IEC 60297
- Vibration & shock tests according to IEC 60068-2
- Corrosion resistance (salt spray) acc. to ISO 9227, ASTM B117
- IP20 according to IEC 60529
- Bonding & ground continuity according to IEC 61010-1
- EU Directive 2011/65/EU (RoHS-2)

Mechanical Properties

Static load capacity	750 kg max.
Dynamic load capacity	562 kg max.
Front door	Detachable, glass, single or double
Rear door	Detachable, solid metal, single or double
Side panels	Detachable, key-locked
Profiles	Front U marking

Mounting

Electrical grounding	Internal parts and frame grounding kit
Cabinet row formation	Aligning baying kit
Locking options	Standard: Mechanical lock Optional: Electronic key-access



Ordering Information

Description	Size	Front Door	Rear Door	Dimensions mm	Color	P/N
Free standing 19" Network Cabinet	26U	Single Glass	Single Solid	600x800	Black	712608S026S-BK51
Free standing 19" Network Cabinet	36U	Single Glass	Single Solid	600x800	Black	712608S036S-BK51
Free standing 19" Network Cabinet	26U	Single Glass	Single Solid	600x1000	Black	712610S026S-BK51
Free standing 19" Network Cabinet	42U	Single Glass	Single Solid	600x1000	Black	712610S042S-BK51
Free standing 19" Network Cabinet	47U	Single Glass	Single Solid	600x1000	Black	712610S047S-BK51
Free standing 19" Network Cabinet	42U	Double Glass	Double Solid	800x800	Black	712808D042D-BK51
Free standing 19" Network Cabinet	42U	Double Perforated	Double Perforated	800x800	Black	712808DP42D-BK51
Free standing 19" Network Cabinet	47U	Double Glass	Double Solid	800x800	Black	712808D047D-BK51
Free standing 19" Network Cabinet	42U	Double Glass	Double Solid	800x1000	Black	712810D042D-BK51
Free standing 19" Network Cabinet	47U	Double Glass	Double Solid	800x1000	Black	712810D047D-BK51
Free standing 19" Network Cabinet	26U	Single Glass	Single Solid	600x800	Gray	712608S026S-GY51
Free standing 19" Network Cabinet	36U	Single Glass	Single Solid	600x800	Gray	712608S036S-GY51
Free standing 19" Network Cabinet	26U	Single Glass	Single Solid	600x1000	Gray	712610S026S-GY51
Free standing 19" Network Cabinet	42U	Single Glass	Single Solid	600x1000	Gray	712610S042S-GY51
Free standing 19" Network Cabinet	47U	Single Glass	Single Solid	600x1000	Gray	712610S047S-GY51
Free standing 19" Network Cabinet	42U	Double Glass	Double Solid	800x800	Gray	712808D042D-GY51
Free standing 19" Network Cabinet	47U	Double Glass	Double Solid	800x800	Gray	712808D047D-GY51
Free standing 19" Network Cabinet	42U	Double Glass	Double Solid	800x1000	Gray	712810D042D-GY51
Free standing 19" Network Cabinet	47U	Double Glass	Double Solid	800x1000	Gray	712810D047D-GY51

Continued on page D.2a

AT&T RackLine

Free Standing Network Cabinets

Description

Free standing 19" network cabinets	
Construction material	Sheet Steel
Size options	26U, 36U, 42U, 45U and 47U (other sizes available)
Width and depth options	600x800mm, 600x1000mm, 800x800mm or 800x1000mm
Color	Black RAL 9005
Accessories	Page D.5.2

Standard & EU Directives Conformance

- Mechanical structure conforming to EN 61587-1, IEC 60917 & IEC 60297
- Vibration & shock tests according to IEC 60068-2
- Corrosion resistance (salt spray) acc. to ISO 9227, ASTM B117
- IP42 according to IEC 60529
- Bonding & ground continuity according to IEC 61010-1
- EU Directive 2011/65/EU (RoHS-2)

Mechanical Properties

Static load capacity	750 kg max.
Dynamic load capacity	562 kg max.
Front door	Detachable, glass, single or double
Rear door	Detachable, solid metal, single or double
Side panels	Detachable, key-locked
Profiles	Front U marking

Mounting

Normal floor or raised floor
Optional raised floor fixing kit

Electrical grounding Internal parts and frame grounding kit

Cabinet row formation

Aligning baying kit

Locking options
Standard: Mechanical lock
Optional: Electronic key-access



Ordering Information

Description	Size	Front Door	Rear Door	Dimensions mm	Color	P/N
Free standing 19" Network Cabinet	26U	Single Glass	Single Solid	600x800	Black	712608S026B-BK51
Free standing 19" Network Cabinet	36U	Single Glass	Single Solid	600x800	Black	712608S036B-BK51
Free standing 19" Network Cabinet	26U	Single Glass	Double Solid	600x1000	Black	712610S026B-BK51
Free standing 19" Network Cabinet	42U	Single Glass	Double Solid	600x1000	Black	712610S042B-BK51
Free standing 19" Network Cabinet	45U	Single Glass	Double Solid	600x1000	Black	712610S045B-BK51
Free standing 19" Network Cabinet	47U	Single Glass	Double Solid	600x1000	Black	712610S047B-BK51
Free standing 19" Network Cabinet	42U	Double Glass	Double Solid	800x800	Black	712808D042B-BK51
Free standing 19" Network Cabinet	45U	Double Glass	Double Solid	800x800	Black	712808D045B-BK51
Free standing 19" Network Cabinet	47U	Double Glass	Double Solid	800x800	Black	712808D047B-BK51
Free standing 19" Network Cabinet	42U	Double Glass	Double Solid	800x1000	Black	712810D042B-BK51
Free standing 19" Network Cabinet	45U	Double Glass	Double Solid	800x1000	Black	712810D045B-BK51
Free standing 19" Network Cabinet	47U	Double Glass	Double Solid	800x1000	Black	712810D047B-BK51

AT&T RackLine

Wall Mount Network Cabinets

Description

Wall mount 19" network cabinets	
Construction material	Sheet Steel
Size options	7U, 9U, 12U, 15U or 18U (other sizes available)
Width and depth	600x560mm
Color	Gray RAL 7035
Accessories	Page D.5.3

Standard & EU Directives Conformance

- Mechanical structure conforming to EN 61587-1, IEC 60917 & IEC 60297
- Vibration & shock tests according to IEC 60068-2
- Corrosion resistance (salt spray) acc. to ISO 9227, ASTM B117
- IP20 according to IEC 60529
- Bonding & ground continuity according to IEC 61010-1
- EU Directive 2011/65/EU (RoHS-2)

Mechanical Properties

Static load capacity	75 kg max.
Front door	Detachable, glass, single
Rear door	Detachable, solid metal, single
Side panels	Detachable, key-locked
Profiles	19" with U marking
Mounting	Wall mount
Electrical grounding	Internal parts and frame grounding kit
Locking options	Mechanical key access



Ordering Information

Description	Size	Dimensions mm	Color	P/N
Wall Mount 19" Network Cabinet	7U	600x560	Gray	7136056007A-GY51
Wall Mount 19" Network Cabinet	9U	600x560	Gray	7136056009A-GY51
Wall Mount 19" Network Cabinet	12U	600x560	Gray	7136056012A-GY51
Wall Mount 19" Network Cabinet	15U	600x560	Gray	7136056015A-GY51
Wall Mount 19" Network Cabinet	18U	600x560	Gray	7136056018A-GY51

AT&T RackLine

Wall Mount SOHO Network Cabinets

Description

Wall mount 19" SOHO (small office-home office) network cabinets

Construction material	Sheet Steel
Size options	7U, 9U or 12U (other sizes available)
Width and depth	520x400mm
Color	Gray RAL 7035
Accessories	Page D.5.4

Standard & EU Directives Conformance

- IP20 according to IEC 60529
- Bonding & ground continuity according to IEC 61010-1
- EU Directive 2011/65/EU (RoHS-2)

Mechanical Properties

Static load capacity	30 kg max.
Front door	Detachable, glass, single
Rear door	Detachable, solid metal, single
Side panels	Detachable, key-locked
Profiles	19" with U marking
Mounting	Wall mount
Electrical grounding	Internal parts and frame grounding kit
Locking options	Mechanical key access



Ordering Information

Description	Size	Dimensions mm	Color	P/N
Wall Mount 19" SOHO Network Cabinet	7U	520x400	Gray	7145240007A-GY51
Wall Mount 19" SOHO Network Cabinet	9U	520x400	Gray	7145240009A-GY51
Wall Mount 19" SOHO Network Cabinet	12U	520x400	Gray	7145240012A-GY51

AT&T RackLine

Enclosures & Rack Systems Server Cabinets Accessories

Description

Accessories for free standing 19" server cabinets
 Cabinet size range 26U, 42U, 45U and 47U
 600x1000 mm and 800x1000 mm

Standard & EU Directives Conformance

- Mechanical structure conforming to EN 61587-1
- Corrosion resistance (salt spray) acc. to ISO 9227, ASTM B117
- EU Directive 2011/65/EU (RoHS-2)



Ordering Information - Vertical Cable Trays

Description	Unit	Height mm	Width mm	Depth mm	Material	Packaging	P/N
Vertical Cable Tray	42U	1855	100	10	Galvanized Metal	1 set = 2 pcs	520181042GA-MT51
Vertical Cable Tray	47U	2000	100	10	Galvanized Metal	1 set = 2 pcs	520201047GA-MT51
Vertical Cable Tray	42U	1855	300	10	Galvanized Metal	1 set = 2 pcs	520183042GA-MT51
Vertical Cable Tray	47U	2000	300	10	Galvanized Metal	1 set = 2 pcs	520203047GA-MT51

Ordering Information - Vertical Cable Managements

Description	Size	Applicable Cabinet Width mm	Color	P/N
Vertical Cable Management for Server & Network Cabinets with Cover	26U	800	Black	715V080026N-BK51
Vertical Cable Management for Server & Network Cabinets with Cover	42U	800	Black	715V080042N-BK51
Vertical Cable Management for Server & Network Cabinets with Cover	45U	800	Black	715V080045N-BK51
Vertical Cable Management for Server & Network Cabinets without Cover	45U	800	Black	715V080045A-BK51
Vertical Cable Management for Server & Network Cabinets with Cover	47U	800	Black	715V080047N-BK51

Ordering Information - Horizontal Cable Managements

Description	Retainers	Units	Height mm	Width mm	Depth mm	Color	Packaging	P/N
Rack-Mount Duct-Type 19" Horizontal Cable Manager	None	1U	44.45	482.60	75.27	Black	1/Box	521NANN075A-BK1U
Rack-Mount Duct-Type 19" Horizontal Cable Manager	Available	1U	44.30	482.00	162.83	Black	1/Box	521NANN162B-BK1U
Rack-Mount Duct-Type 19" Horizontal Cable Manager	Available	2U	88.80	484.84	107.03	Black	1/Box	521NANN107B-BK2U
Rack-Mount Duct-Type 19" Horizontal Cable Manager	Available	2U	88.80	484.74	171.62	Black	1/Box	521NANN171B-BK2U
Rack-Mount Ring-Type 19" Horizontal Cable Manager	None	1U	44.45	482.60	65.00	Black	1/Box	521NANN065C-BK1U

Continued on page D.5.1a

AT&T RackLine

Enclosures & Rack Systems Server Cabinets Accessories (contd.)

Ordering Information - PDU Brackets

Description	Size	Contents	Color	P/N
Fixing Tray for Zero U PDU	N/A	1 Set = 2 Pieces	Black	415D00102NA-BK51
Fixing Tray for Zero U PDU	42U	1 Set = 1 Piece	Black	415D42101NA-BK51
Fixing Tray for Zero U PDU	47U	1 Set = 1 Piece	Black	415D47101NA-BK51

Ordering Information - Grounding Kits

Description	Cable/Bar Cross-Section mm ²	Contents	P/N
RackLine Doors and Covers Grounding Kit	6.0	7 Cables	715E06007NA-NS51
Cabinet Frame Grounding Kit	25	1 Cable	415E25001NA-NS51
Cabinet 10kA Grounding & Equalizing 19" Bar	30 (2x15)	1 Unit	715E30100NA-NS51

Ordering Information - Brush Kits

Description	Contents	Applicable Cabinet Dimensions mm	Color	P/N
Brush Kit for Cable Entry	6 Brushes	600x1000	Black	715SBK006NA-BK51
Brush Kit for Cable Entry	12 Brushes	800x1000	Black	715SBK012NA-BK51

Ordering Information - Leveling Feet

Description	Contents	Thread	Height Range	P/N
Adjustable Leveling Feet	1 Set = 4 Pieces	M12x1.75 Course	0-30mm	415FM120410-NS51

Ordering Information - Caster Set

Description	Contents	Breaking Option	Type	Color	P/N
RackLine Caster Set (Wheels)	1 Set = 4 Pieces	Two Front Wheels	Swivel	Metal	715GRCN104A-MT51

Ordering Information - Baying Kits

Description	Contents	Color	P/N
RackLine Baying Kit	1 Set = 6 Pieces	Black	715HBK106NA-BK51
RackLine Baying Kit	1 Set = 6 Pieces	Gray	715HBK106NA-GY51

Ordering Information - Floor Anchor Kits

Description	Contents	Color	P/N
L-Shape RackLine Floor Anchor Kit	1 Set = 4 Pieces	Black	715KLSA104A-BK51
L-Shape RackLine Floor Anchor Kit	1 Set = 4 Pieces	Gray	715KLSA104A-GY51

Ordering Information - Nuts, Washers and Screws

Description	Contents	Thread	Color	P/N
Nuts, Washers and Screws Set	1 Set = 4 Pieces	M6x1.5 Course	Black	415NNWS104A-BK51
Nuts, Washers and Screws Set	1 Set = 20 Pieces	M6x1.5 Course	Black	415NNWS120A-BK51
Nuts, Washers and Screws Set	1 Set = 50 Pieces	M6x1.5 Course	Black	415NNWS150A-BK51

Continued on page D.5.1b

AT&T RackLine

Enclosures & Rack Systems Server Cabinets Accessories (contd.)

Ordering Information - Shelves

Description	Size	Depth mm	Max. Load kg	Type	Color	P/N
19" Vented Steel Shelf	1U	250	15	Fixed	Black	715PFS1251A-BK51
19" Vented Steel Shelf	1U	250	15	Fixed	Gray	715PFS1251A-GY51
19" Vented Steel Shelf	1U	450	20	Fixed	Black	715PFS1452A-BK51
19" Vented Steel Shelf	1U	450	20	Fixed	Gray	715PFS1452A-GY51
Vented Steel Shelf with Support Profiles	0.5U	800	50	Fixed	Black	715PFS0805A-BK51
Vented Steel Shelf with Support Profiles	0.5U	800	50	Fixed	Gray	715PFS0805A-GY51
Vented Steel Shelf with Support Profiles	0.5U	800	50	Sliding	Black	715PSS0805A-BK51
Vented Steel Shelf with Support Profiles	0.5U	800	50	Sliding	Gray	715PSS0805A-GY51
19" Heavy-Duty Steel Shelf	1U	800	80	Fixed	Black	715PFS1808A-BK51
19" Heavy-Duty Steel Shelf	1U	800	80	Fixed	Gray	715PFS1808A-GY51
19" Heavy-Duty Telescopic Sliding Steel Shelf	1U	800	80	Sliding	Black	715PSS1808A-BK51
19" Heavy-Duty Telescopic Sliding Steel Shelf	1U	800	80	Sliding	Gray	715PSS1808A-GY51
19" Heavy-Duty Fixed Vented Steel Shelf with Support Profiles	1U	1000	80	Fixed	Black	415PFS1108A-BK51
19" Heavy-Duty Fixed Vented Steel Shelf with Support Profiles	1U	1000	80	Fixed	Gray	415PFS1108A-GY51
19" Heavy-Duty Telescopic Sliding Vented Steel Shelf	1U	1000	80	Sliding	Black	415PSS1108A-BK51
19" Heavy-Duty Telescopic Sliding Vented Steel Shelf	1U	1000	80	Sliding	Gray	415PSS1108A-GY51

Ordering Information - Blank Rack Spacers

Description	Size	Color	P/N
19" Metal Blank Rack Spacer	1U	Black	415RBRS001A-BK51
19" Metal Blank Rack Spacer	2U	Black	415RBRS002A-BK51
19" Metal Blank Rack Spacer	4U	Black	415RBRS004A-BK51
19" Metal Blank Rack Spacer	8U	Black	415RBRS008A-BK51
19" Metal Blank Rack Spacer	16U	Black	415RBRS016A-BK51
19" Metal Blank Rack Spacer	24U	Black	415RBRS024A-BK51

Ordering Information - Air Removal Units

Description	Fans Count	Fan Lifetime Hours	Fan Protection	Thermostat Type	Applicable Cabinet Dimensions Depth mm	P/N
Air Removal Unit with Thermostat	2	60,000	Inductive & Fuse	Bimetal Contact	Server Cabinet D= 1000	715ARUT002A-NS51
Air Removal Unit with Thermostat	4	60,000	Inductive & Fuse	Bimetal Contact	Server Cabinet D= 1000	715ARUT004A-NS51
Air Removal Unit with Thermostat	6	60,000	Inductive & Fuse	Bimetal Contact	Server Cabinet D= 1000	715ARUT006A-NS51

Ordering Information - Plinths

Description	Height mm	Applicable Cabinet Dimensions mm	Color	P/N
Plinth for Server & Network Cabinets	100	600x1000	Black	715PL16010A-BK51
Plinth for Server & Network Cabinets	100	600x1000	Gray	715PL16010A-GY51
Plinth for Server & Network Cabinets	100	800x1000	Black	715PL18010A-BK51
Plinth for Server & Network Cabinets	100	800x1000	Gray	715PL18010A-GY51

Note: All plinths are compatible with Caster Set P/N 715GRCN104A-MT51

AT&T RackLine

Enclosures & Rack Systems Network Cabinets Accessories

Description

Accessories for free standing 19" network cabinets
 Cabinet size range 26U, 36U, 42U, 45U and 47U
 600x800 mm, 600x1000 mm
 800x800 mm, 800x1000mm

Standard & EU Directives Conformance

- Mechanical structure conforming to EN 61587-1
- Corrosion resistance (salt spray) acc. to ISO 9227, ASTM B117
- EU Directive 2011/65/EU (RoHS-2)



Ordering Information - Vertical Cable Trays

Description	Unit	Height mm	Width mm	Depth mm	Material	Packaging	P/N
Vertical Cable Tray	42U	1855	100	10	Galvanized Metal	1 set = 2 pcs	520181042GA-MT51
Vertical Cable Tray	47U	2000	100	10	Galvanized Metal	1 set = 2 pcs	520201047GA-MT51
Vertical Cable Tray	42U	1855	300	10	Galvanized Metal	1 set = 2 pcs	520183042GA-MT51
Vertical Cable Tray	47U	2000	300	10	Galvanized Metal	1 set = 2 pcs	520203047GA-MT51

Ordering Information - Vertical Cable Managements

Description	Size	Applicable Cabinet Width mm	Color	P/N
Vertical Cable Management for Server & Network Cabinets with Cover	26U	800	Black	715V080026N-BK51
Vertical Cable Management for Server & Network Cabinets with Cover	36U	800	Black	715V080036N-BK51
Vertical Cable Management for Server & Network Cabinets with Cover	42U	800	Black	715V080042N-BK51
Vertical Cable Management for Server & Network Cabinets with Cover	45U	800	Black	715V080045N-BK51
Vertical Cable Management for Server & Network Cabinets without Cover	45U	800	Black	715V080045A-BK51
Vertical Cable Management for Server & Network Cabinets with Cover	47U	800	Black	715V080047N-BK51

Ordering Information - Horizontal Cable Managements

Description	Retainers	Units	Height mm	Width mm	Depth mm	Color	Packaging	P/N
Rack-Mount Duct-Type 19" Horizontal Cable Manager	None	1U	44.45	482.60	75.27	Black	1/Box	521NANN075A-BK1U
Rack-Mount Duct-Type 19" Horizontal Cable Manager	Available	1U	44.30	482.00	162.83	Black	1/Box	521NANN162B-BK1U
Rack-Mount Duct-Type 19" Horizontal Cable Manager	Available	2U	88.80	484.84	107.03	Black	1/Box	521NANN107B-BK2U
Rack-Mount Duct-Type 19" Horizontal Cable Manager	Available	2U	88.80	484.74	171.62	Black	1/Box	521NANN171B-BK2U
Rack-Mount Ring-Type 19" Horizontal Cable Manager	None	1U	44.45	482.60	65.00	Black	1/Box	521NANN065C-BK1U

Continued on page D.5.2a

AT&T RackLine

Enclosures & Rack Systems Network Cabinets Accessories (contd.)

Ordering Information - PDU Brackets

Description	Size	Contents	Color	P/N
Fixing Tray for Zero U PDU	N/A	1 Set = 2 Pieces	Black	415D00102NA-BK51
Fixing Tray for Zero U PDU	42U	1 Set = 1 Piece	Black	415D42101NA-BK51
Fixing Tray for Zero U PDU	47U	1 Set = 1 Piece	Black	415D47101NA-BK51

Ordering Information - Ground Kits

Description	Cable/Bar Cross-Section mm ²	Contents	P/N
RackLine Doors and Covers Grounding Kit	6.0	4 Cables	715E06004NA-NS51
RackLine Doors and Covers Grounding Kit	6.0	6 Cables	715E06006NA-NS51
RackLine Doors and Covers Grounding Kit	6.0	7 Cables	715E06007NA-NS51
Cabinet Frame Grounding Kit	25	1 Cable	415E25001NA-NS51
Cabinet 10kA Grounding & Equalizing 19" Bar	30 (2x15)	1 Unit	715E30100NA-NS51

Ordering Information - Brush Kits

Description	Contents	Applicable Cabinet Dimensions mm	Color	P/N
Brush Kit for Cable Entry	4 Brushes	600x800	Black	715SBK004NB-BK51
Brush Kit for Cable Entry	6 Brushes	600x1000	Black	715SBK006NA-BK51
Brush Kit for Cable Entry	10 Brushes	800x800	Black	715SBK010NB-BK51
Brush Kit for Cable Entry	12 Brushes	800x1000	Black	715SBK012NA-BK51

Ordering Information - Leveling Feet

Description	Contents	Thread	Height Range	P/N
Adjustable Leveling Feet	1 Set = 4 Pieces	M12x1.75 Course	0-30mm	415FM120410-NS51

Ordering Information - Caster Set

Description	Contents	Breaking Option	Type	Color	P/N
RackLine Caster Set (Wheels)	1 Set = 4 Pieces	Two Front Wheels	Swivel	Metal	715GRCN104A-MT51

Ordering Information - Baying Kits

Description	Contents	Color	P/N
RackLine Baying Kit	1 Set = 6 Pieces	Black	715HBK106NA-BK51
RackLine Baying Kit	1 Set = 6 Pieces	Gray	715HBK106NA-GY51

Ordering Information - Floor Anchor Kits

Description	Contents	Color	P/N
L-Shape RackLine Floor Anchor Kit	1 Set = 4 Pieces	Black	715KLSA104A-BK51
L-Shape RackLine Floor Anchor Kit	1 Set = 4 Pieces	Gray	715KLSA104A-GY51

Ordering Information - Nuts, Washers and Screws

Description	Contents	Thread	Color	P/N
Nuts, Washers and Screws Set	1 Set = 4 Pieces	M6x1.5 Course	Black	415NNWS104A-BK51
Nuts, Washers and Screws Set	1 Set = 20 Pieces	M6x1.5 Course	Black	415NNWS120A-BK51
Nuts, Washers and Screws Set	1 Set = 50 Pieces	M6x1.5 Course	Black	415NNWS150A-BK51

Continued on page D.5.2b

AT&T RackLine

Enclosures & Rack Systems Network Cabinets Accessories (contd.)

Ordering Information - Shelves

Description	Size	Depth mm	Max. Load kg	Type	Color	P/N
19" Vented Steel Shelf	1U	250	15	Fixed	Black	715PFS1251A-BK51
19" Vented Steel Shelf	1U	250	15	Fixed	Gray	715PFS1251A-GY51
19" Vented Steel Shelf	1U	450	20	Fixed	Black	715PFS1452A-BK51
19" Vented Steel Shelf	1U	450	20	Fixed	Gray	715PFS1452A-GY51
Vented Steel Shelf with Support Profiles	0.5U	800	50	Fixed	Black	715PFS0805A-BK51
Vented Steel Shelf with Support Profiles	0.5U	800	50	Fixed	Gray	715PFS0805A-GY51
Vented Steel Shelf with Support Profiles	0.5U	800	50	Sliding	Black	715PSS0805A-BK51
Vented Steel Shelf with Support Profiles	0.5U	800	50	Sliding	Gray	715PSS0805A-GY51
19" Heavy-Duty Steel Shelf	1U	800	80	Fixed	Black	715PFS1808A-BK51
19" Heavy-Duty Steel Shelf	1U	800	80	Fixed	Gray	715PFS1808A-GY51
19" Heavy-Duty Telescopic Sliding Steel Shelf	1U	800	80	Sliding	Black	715PSS1808A-BK51
19" Heavy-Duty Telescopic Sliding Steel Shelf	1U	800	80	Sliding	Gray	715PSS1808A-GY51
19" Heavy-Duty Fixed Vented Steel Shelf with Support Profiles	1U	1000	80	Fixed	Black	415PFS1108A-BK51
19" Heavy-Duty Fixed Vented Steel Shelf with Support Profiles	1U	1000	80	Fixed	Gray	415PFS1108A-GY51
19" Heavy-Duty Telescopic Sliding Vented Steel Shelf	1U	1000	80	Sliding	Black	415PSS1108A-BK51
19" Heavy-Duty Telescopic Sliding Vented Steel Shelf	1U	1000	80	Sliding	Gray	415PSS1108A-GY51

Ordering Information - Blank Rack Spacers

Description	Size	Color	P/N
19" Metal Blank Rack Spacer	1U	Black	415RBRS001A-BK51
19" Metal Blank Rack Spacer	2U	Black	415RBRS002A-BK51
19" Metal Blank Rack Spacer	4U	Black	415RBRS004A-BK51
19" Metal Blank Rack Spacer	8U	Black	415RBRS008A-BK51
19" Metal Blank Rack Spacer	16U	Black	415RBRS016A-BK51
19" Metal Blank Rack Spacer	24U	Black	415RBRS024A-BK51

Ordering Information - Air Removal Units

Description	Fans Count	Fan Lifetime Hours	Fan Protection	Thermostat Type	Applicable Cabinet Dimensions Depth mm	P/N
Air Removal Unit with Thermostat	2	60,000	Inductive & Fuse	Bimetal Contact	Network Cabinet D < 1000	715ARUT002N-NS51
Air Removal Unit with Thermostat	4	60,000	Inductive & Fuse	Bimetal Contact	Network Cabinet D < 1000	715ARUT004N-NS51
Air Removal Unit with Thermostat	2	60,000	Inductive & Fuse	Bimetal Contact	Network Cabinet D = 1000	715ARUT002A-NS51
Air Removal Unit with Thermostat	4	60,000	Inductive & Fuse	Bimetal Contact	Network Cabinet D = 1000	715ARUT004A-NS51
Air Removal Unit with Thermostat	6	60,000	Inductive & Fuse	Bimetal Contact	Network Cabinet D = 1000	715ARUT006A-NS51

Ordering Information - Plinths

Description	Height mm	Applicable Cabinet Dimensions mm	Color	P/N
Plinth for Server & Network Cabinets	100	600x800	Black	715PL16008A-BK51
Plinth for Server & Network Cabinets	100	600x800	Gray	715PL16008A-GY51
Plinth for Server & Network Cabinets	100	600x1000	Black	715PL16010A-BK51
Plinth for Server & Network Cabinets	100	600x1000	Gray	715PL16010A-GY51
Plinth for Server & Network Cabinets	100	800x800	Black	715PL18008A-BK51
Plinth for Server & Network Cabinets	100	800x800	Gray	715PL18008A-GY51
Plinth for Server & Network Cabinets	100	800x1000	Black	715PL18010A-BK51
Plinth for Server & Network Cabinets	100	800x1000	Gray	715PL18010A-GY51

Note: All plinths are compatible with Caster Set P/N 715GRCN104A-MT51

AT&T RackLine

Enclosures & Rack Systems Wall-Mount Network Cabinets Accessories

Description

Accessories for wall-mount network cabinets
 Cabinet size range 7U, 9U, 12U, 15U, 18U
 600x560 mm

Standard & EU Directives Conformance

- Mechanical structure conforming to EN 61587-1
- Corrosion resistance (salt spray) acc. to ISO 9227, ASTM B117
- EU Directive 2011/65/EU (RoHS-2)



Ordering Information - Horizontal Cable Managements

Description	Retainers	Units	Height mm	Width mm	Depth mm	Color	Packaging	P/N
Rack-Mount Duct-Type 19" Horizontal Cable Manager	None	1U	44.45	482.60	75.27	Black	1/Box	521NANN075A-BK1U
Rack-Mount Duct-Type 19" Horizontal Cable Manager	Available	1U	44.30	482.00	162.83	Black	1/Box	521NANN162B-BK1U
Rack-Mount Duct-Type 19" Horizontal Cable Manager	Available	2U	88.80	484.84	107.03	Black	1/Box	521NANN107B-BK2U
Rack-Mount Duct-Type 19" Horizontal Cable Manager	Available	2U	88.80	484.74	171.62	Black	1/Box	521NANN171B-BK2U
Rack-Mount Ring-Type 19" Horizontal Cable Manager	None	1U	44.45	482.60	65.00	Black	1/Box	521NANN065C-BK1U

Ordering Information - Grounding Kits

Description	Cable/Bar Cross-Section mm ²	Contents	P/N
RackLine Doors and Covers Grounding Kit	6.0	3 Cables	715E06003NA-NS51
Cabinet 10kA Grounding & Equalizing 19" Bar	30 (2x15)	1 Unit	715E30100NA-NS51

Continued on page D.5.3a

AT&T RackLine

Enclosures & Rack Systems Wall-Mount Network Cabinets Accessories (contd.)

Ordering Information - Brush Kits

Description	Contents	Applicable Cabinet Dimensions mm	Color	P/N
Brush Kit for Cable Entry	1 Brush	600x560	Black	715SBK001NC-BK51

Ordering Information - Nuts, Washers and Screws

Description	Contents	Thread	Color	P/N
Nuts, Washers and Screws Set	1 Set = 4 Pieces	M6x1.5 Course	Black	415NNWS104A-BK51
Nuts, Washers and Screws Set	1 Set = 20 Pieces	M6x1.5 Course	Black	415NNWS120A-BK51
Nuts, Washers and Screws Set	1 Set = 50 Pieces	M6x1.5 Course	Black	415NNWS150A-BK51

Ordering Information - Shelves

Description	Size	Depth mm	Max. Load kg	Type	Color	P/N
19" Vented Steel Shelf	1U	250	15	Fixed	Gray	715PFS1251A-GY51
19" Vented Steel Shelf	1U	450	20	Fixed	Gray	715PFS1452A-GY51

Ordering Information - Blank Rack Spacers

Description	Size	Color	P/N
19" Metal Blank Rack Spacer	1U	Black	415RBRS001A-BK51
19" Metal Blank Rack Spacer	2U	Black	415RBRS002A-BK51
19" Metal Blank Rack Spacer	4U	Black	415RBRS004A-BK51

Ordering Information - Air Removal Units

Description	Fans Count	Fan Lifetime hours	Fan Protection	Thermostat Type	P/N
Air Removal Unit with Thermostat	1	60,000	Inductive & Fuse	Bimetal Contact	715ARUT001S-NS51
Air Removal Unit with Thermostat	2	60,000	Inductive & Fuse	Bimetal Contact	715ARUT002S-NS51

AT&T RackLine

Enclosures & Rack Systems SOHO Network Cabinets Accessories

Description

Accessories for SOHO network cabinets
 Cabinet size range 7U, 9U, 12U
 520x400 mm

Standard & EU Directives Conformance

- Mechanical structure conforming to EN 61587-1
- Corrosion resistance (salt spray) acc. to ISO 9227, ASTM B117
- EU Directive 2011/65/EU (RoHS-2)



Ordering Information - Horizontal Cable Managements

Description	Retainers	Units	Height mm	Width mm	Depth mm	Color	Packaging	P/N
Rack-Mount Duct-Type 19" Horizontal Cable Manager	None	1U	44.45	482.60	75.27	Black	1/Box	521NANN075A-BK1U
Rack-Mount Duct-Type 19" Horizontal Cable Manager	Available	1U	44.30	482.00	162.83	Black	1/Box	521NANN162B-BK1U
Rack-Mount Duct-Type 19" Horizontal Cable Manager	Available	2U	88.80	484.84	107.03	Black	1/Box	521NANN107B-BK2U
Rack-Mount Duct-Type 19" Horizontal Cable Manager	Available	2U	88.80	484.74	171.62	Black	1/Box	521NANN171B-BK2U
Rack-Mount Ring-Type 19" Horizontal Cable Manager	None	1U	44.45	482.60	65.00	Black	1/Box	521NANN065C-BK1U

Ordering Information - Brush Kit

Description	Contents	Applicable Cabinet Dimensions mm	Color	P/N
SOHO Brush Kit for Cable Entry	1 Brush	520x400	Black	715SBK001ND-BK51

Ordering Information - Nuts, Washers and Screws

Description	Contents	Thread	Color	P/N
Nuts, Washers and Screws Set	1 Set = 4 Pieces	M6x1.5 Course	Black	415NNWS104A-BK51
Nuts, Washers and Screws Set	1 Set = 20 Pieces	M6x1.5 Course	Black	415NNWS120A-BK51
Nuts, Washers and Screws Set	1 Set = 50 Pieces	M6x1.5 Course	Black	415NNWS150A-BK51

Continued on page D.5.4a

AT&T RackLine

Enclosures & Rack Systems SOHO Network Cabinets Accessories (contd.)

Ordering Information - Shelves

Description	Size	Depth mm	Max. Load kg	Type	Color	P/N
19" Vented Steel Shelf	1U	250	15	Fixed	Gray	715PFS1251A-GY51

Ordering Information - Blank Rack Spacers

Description	Size	Color	P/N
19" Metal Blank Rack Spacer	1U	Black	415RBRS001A-BK51
19" Metal Blank Rack Spacer	2U	Black	415RBRS002A-BK51

Ordering Information - Air Removal Units

Description	Fans Count	Fan Lifetime hours	Fan Protection	Thermostat Type	P/N
Air Removal Unit with Thermostat	1	60,000	Inductive & Fuse	Bimetal Contact	715ARUT001S-NS51
Air Removal Unit with Thermostat	2	60,000	Inductive & Fuse	Bimetal Contact	715ARUT002S-NS51

AT&T RackLine

Basic Power Distribution Units (PDU)

Description

Basic power distribution units for racks and cabinets	
Nominal input voltage	250V AC single phase
Optional rated current	10A, 13A, 16A or 32A
Optional power plug types	IEC 60309, DIN 49441 or BS 1363 with 3m line cord
Output sockets	CEE 7/4 ("Schuko"), BS 1363 or IEC 60320 Type C13
Power switch	Circuit breaker

Standard & EU Directives Conformance

- EN-55022 Class B (EMC)
- EU 2006/95/EC (LVD)
- EU 2011/65/EU (RoHS-2)
- IEC 60950 Para. 2.1 (Electrical safety)

Features and Properties

Mounting options	1U, 2U and Zero U rack mount
Material	Extruded aluminum chassis
Color	Black
Circuit breaker	10A or 16A with safety cover



Ordering Information

Description	Plug Type	CEE 7/4 Schuko Sockets	BS 1363 Sockets	IEC 60320 Type C13 Sockets	Circuit Breakers	Size	Dimensions mm	P/N
10A 1U Basic PDU	BS 1363	None	None	6	1x10A	1U	483x44x44	61410A1U06A-BK51
16A 1U Basic PDU	DIN 49441	6	None	None	1x16A	1U	483x44x44	61416A1U06A-BK51
16A 1U Basic PDU	IEC 60309	None	None	10	1x16A	1U	483x44x44	61416A1U10A-BK51
16A 2U Basic PDU	DIN 49441	9	None	None	1x16A	2U	483x89x44	61416A2U09A-BK51
13A 1U Basic PDU	BS 1363	None	6	None	On/Off	1.5U	483x67x44	61413A1U06A-BK51
32A Zero U Basic PDU	IEC 60309	18	None	None	2x16A	Zero U	1612x44x66	61432A0U18A-BK51
32A Zero U Basic PDU	IEC 60309	24	None	None	2x16A	Zero U	1612x44x66	61432A0U24A-BK51
32A 1U Basic PDU	IEC 60309	None	None	10	1x32A	1U	483x44x44	61432A1U10A-BK51



AT&T

AT&T Cabling Systems Headquarters

Hohenstaufenring 62
50674 Cologne
Germany
T: +49.221.288.8337
F: +49.221.288.8342
www.att.com/cabling
Sales & Customer Support:
info_emea@cabling.att-mail.com
Technical support:
tech.support_emea@cabling.att-mail.com

AT&T Corporate Headquarters

208 South Akard St.
Dallas, TX 75202
USA

© 2020 AT&T Cabling Systems. All rights reserved.

AT&T Authorized Licensee. AT&T, the AT&T Globe Design and all other AT&T marks contained herein are trademarks of AT&T Intellectual Property and/or AT&T affiliated companies.

Issue 2.3 11/8/2017.

AT&T CopperLine™, AT&T FiberLine™, AT&T CenterLine™, AT&T RackLine™, AT&T OutdoorLine™, AT&T Port-LockLine™, AT&T CablingGuard™, AFOE™ and AT&T Millennium™ are trademarks of AT&T Cabling Systems.