

AT&T CopperLine Panels

Unshielded Snap-in Blank Patch Panels for Straight Jacks

Description


24 & 48 port unshielded blank 19" panels	
KSJ type compatibility	Unshielded 180° straight RJ45 jacks
Category compatibility	CAT5e CAT6 CAT6A
KSJ insertion method	Back loading
Formation	24 ports in one row
Front cable organizer	Removable modular rings
Back cable organizer	Folding frame with snap-in cable grips
Shield	None

Standard & EU Directives Conformance

- UL94 V-0 flame test
- EU Directive 2011/65/EU (RoHS-2)

Mechanical Properties and Features

Frame	Galvanized corrosion resistant steel
Paint	Powder paint finish
Operating temperature	-20 to +60C at 5-95% RH (non condensing)
Storage temperature	-20 to +80C
Plastic parts	High-impact flame retardant materials
Port identification	Labels with transparent plastic cover
Panel identification	Designated space at the panel front



Ordering Information

Description	Color	Units	Size mm	Packaging	P/N
24 Port Unshielded 19" Snap-in Blank Patch Panel (Straight Jacks)	Steel-Blue	1U	44.4x483	1/Box	13U00NV024A-SB1U
48 Port Unshielded 19" Snap-in Blank Patch Panel (Straight Jacks)	Steel-Blue	2U	89.0x483	1/Box	13U00NV048A-SB2U