

AT&T CopperLine Outlets

LJ6C (UK) Style Faceplates

Description

1-4 port LJ6C Style faceplates

Jack compatibility	Shielded or unshielded RJ45 keystone jacks
Category compatibility	CAT5e CAT6 CAT6A
Mount type	Wall or ducts
Shuttered	Yes
Color	White (other colors available)
KSJ insertion method	Back loading

Standard & EU Directives Conformance

- UL94 V-0 flame test
- EU Directive 2011/65/EU (RoHS-2)

Mechanical Properties and Features

Material of construction	High-impact flame retardant materials
Operating temperature	-20 to +60C at 5-95% RH (non condensing)
Storage temperature	-20 to +80C



Ordering Information

Description	Color	Ports	Size mm	Labeling	Packaging	P/N
LJ6C Style Standard Shallow Back Box	White	N/A	87x87x28	None	1/Bag	16L00NV000A-WT61
LJ6C Style Standard Deep Back Box	White	N/A	87x87x42	None	1/Bag	16L00NV000B-WT61
LJ6C Style Wide Shallow Back Box	White	N/A	147x87x28	None	1/Bag	16L00NV000C-WT61
LJ6C Style Wide Deep Back Box	White	N/A	147x87x42	None	1/Bag	16L00NV000D-WT61
LJ6C Style Standard Faceplate for A Single Module	White	N/A	86x86x9	None	1/Bag	16L00NV000E-WT61
LJ6C Style Standard Faceplate for Two Modules	White	N/A	86x86x9	None	1/Bag	16L00NV000F-WT61
LJ6C Style Wide Faceplate for Four Modules	White	N/A	146x86x9	None	1/Bag	16L00NV000G-WT61
LJ6C Style Flat Module	White	1	38x25	Station ID	1/Bag	16L00NV001A-WT61
LJ6C Style Angled Module	White	1	38x25	Station ID	1/Bag	16L00NV001B-WT61
LJ6C Style Blank Flat Module	White	0	38x25	None	1/Bag	16L00NV000H-WT61