

AT&T CopperLine Category 3

Unshielded & Shielded Keystone Jacks

Description


4-10 wire unshielded or shielded jacks	
Frequency range	1-16 MHz
Compatible conductors	23-26 AWG Solid or stranded
Pin-pair assignment	T568A & T568B (Universal)
Contacts	Gold plating over nickel plated metal
Shield	Corrosion resistant metal casing
Housing	High impact FR compound

Standard & EU Directives Conformance

- Connectors according to IEC 60603-7
- Category 3 connecting hardware acc. to ANSI/TIA-568.2-D
- UL94 V-0 flame test
- EU Directive 2011/65/EU (RoHS-2)

Mechanical & Electrical Properties

Orientation	90°
IDC contacts	Punch-down 110 or LSA-Plus
Insertion/Extraction durability	750 cycles Level A durability
Cable re-termination	20 terminations
Operating temperature	-20 to +60C at 5-95% RH (non condensing)
Contact resistance	20 mOhm max.
DC resistance	0.1 Ohm max.
Voltage rating	72 Vdc max.
Insulation resistance	500 MegaOhm min. @500 Vdc



Ordering Information

Description	Color	Packaging		P/N
4P4C RJ11 Unshielded CAT3 Keystone Jack	White	1/Bag	100/Box	15A03NV004N-WT5C
4P4C RJ11 Shielded CAT3 Keystone Jack	White	1/Bag	100/Box	15C03NV004N-WT5C
6P4C RJ11 Unshielded CAT3 Keystone Jack	White	1/Bag	100/Box	15A03NV004A-WT5C
6P4C RJ11 Shielded CAT3 Keystone Jack	White	1/Bag	100/Box	15C03NV004A-WT5C
6P6C RJ12 Unshielded CAT3 Keystone Jack	White	1/Bag	100/Box	15A03NV006N-WT5C
6P6C RJ12 Shielded CAT3 Keystone Jack	White	1/Bag	100/Box	15C03NV006N-WT5C
8P8C RJ45 Unshielded CAT3 Keystone Jack	White	1/Bag	100/Box	15A03NV008N-WT5C
8P8C RJ45 Shielded CAT3 Keystone Jack	White	1/Bag	100/Box	15C03NV008N-WT5C
10P10C RJ50 Unshielded CAT3 Keystone Jack	White	1/Bag	100/Box	15A03NV010N-WT5C
10P10C RJ50 Shielded CAT3 Keystone Jack	White	1/Bag	100/Box	15C03NV010N-WT5C