

AT&T CopperLine Category 7A S/FTP 100 Ohm Horizontal Indoor LAN Cables

Description

4 & 8 pair S/FTP cables	
Operation frequency range	1-1000 MHz
Testing frequency range	1-1200 MHz
Conductor	22 AWG Solid bare copper
Insulation	PO
Color code	Modified ANSI/TIA-568.2-D (solid colors)
Individual pair shield	Aluminum foil
Overall shield	Tin-coated copper braid
Drain wire	Per request
Jacket	LS0H

Standards, EU Directives and Regulations Conformance

- Category 7A cable according to IEC 61156-5
- 1000MHz cable according to EN 50288-11
- IEC 60332-1, IEC 60332-3-24 or IEC 60332-3-25 flame tests
- IEC 60754 & IEC 61034
- EU Directive 2011/65/EU (RoHS-2)
- EU Regulation 305/2011 (CPR):
Various classifications available upon request.

Mechanical & Electrical Properties

Pulling force	50 N/mm ² max.
Short term bend radius	8xOD mm
Long term bend radius	4xOD mm
Operating temperature	-20 to +60C
Installation temperature	0 to +50C
DC resistance	62 Ohm/km max.
Capacitance	56 max. pF/m @ 1kHz
Voltage rating	72 Vdc max.
Velocity of propagation (NVP)	78% nom.



Ordering Information

Description	Color	Flame Test	OD mm	Weight kg/km	P/N
4-Pair 22 AWG S/FTP CAT7A LS0H-1 Cable	Gray RAL 9002	IEC 60332-1	7.6	61	11S7AHA004N-GYxx-yy
4-Pair 22 AWG S/FTP CAT7A LS0H-3 Cable	Gray RAL 9002	IEC 60332-3-24	7.9	67	11S7AHC004N-GYxx-yy
8-Pair 22 AWG S/FTP CAT7A LS0H-1 Cable	Gray RAL 9002	IEC 60332-1	7.6x15.2	122	11S7AHA008N-GYxx-yy
8-Pair 22 AWG S/FTP CAT7A LS0H-3 Cable	Gray RAL 9002	IEC 60332-3-24	7.9x16.0	134	11S7AHC008N-GYxx-yy

Packaging options (xx): 2K: 500m Drums, 2L: 1000m Drums. Additional options available upon request.
CPR class options (yy): B1: B2ca, C1: Cca, D1: Dca, E1: Eca, F1: Fca. Sub class information detailed in technical specifications.