

AT&T FiberLine Panels

Basic 19" Fiber Optic Panels

Description

1-48 fiber 1U low-cost fixed 19" fiber optic splicing/distribution panels

Connector type compatibility - Group A ST, SC, FC, LC, MTRJ, LSH (E-2000™)

Splicing Up to two 24 fiber splicing cassettes

Distribution Up to 48 fiber direct cable termination

Panel access Top and front sliding tray

Back Cable Management None

Front Cable Management None

Standard & EU Directives Conformance

- Relevant sections of ANSI/TIA/EIA-604 (FOCIS)
- Relevant sections of IEC 60874
- Relevant sections of IEC 61753
- Relevant sections of IEC 61754
- Plastic parts: UL94 V-0 flame test
- EU Directive 2011/65/EU (RoHS-2)

Mechanical Properties and Features

Frame	SPCC Steel, colored black
Front cover	None
Operating temperature	-10 to +60C at 5-85% RH (non condensing)
Storage temperature	-40 to +70C
Plastic parts	High-impact flame retardant materials
Port identification	Numbers and designated space printed on the cover



Ordering Information

Description	Compatible Couplers	Coupler Capacity	Fiber Capacity	Cassette Capacity	Size mm	Packaging	P/N
Basic 1U Blank 19" Fiber Optic Panel	ST Simplex	24	24	1	44.5x483x230	1/Box	27B00NV024A-BK1U
Basic 1U Blank 19" Fiber Optic Panel	SC Simplex	24	24	1	44.5x483x230	1/Box	27B00NV024H-BK1U
Basic 1U Blank 19" Fiber Optic Panel	SC Duplex	12	24	1	44.5x483x230	1/Box	27B00NV024J-BK1U
Basic 1U Blank 19" Fiber Optic Panel	SC Duplex	24	48	2	44.5x483x230	1/Box	27B00NV048J-BK1U
Basic 1U Blank 19" Fiber Optic Panel	FC Simplex	24	24	1	44.5x483x230	1/Box	27B00NV024E-BK1U
Basic 1U Blank 19" Fiber Optic Panel	LC Duplex	12	24	1	44.5x483x230	1/Box	27B00NV024Q-BK1U
Basic 1U Blank 19" Fiber Optic Panel	LC Duplex	24	48	2	44.5x483x230	1/Box	27B00NV048Q-BK1U
Basic 1U Blank 19" Fiber Optic Panel	MTRJ	12	24	1	44.5x483x230	1/Box	27B00NV024S-BK1U
Basic 1U Blank 19" Fiber Optic Panel	MTRJ	24	48	1	44.5x483x230	1/Box	27B00NV048S-BK1U