

AT&T CenterLine

RCE Free Standing Network Cabinets

Description

Free standing 19" network cabinets for IT Rooms and data centers

| | |
|-------------------------|--|
| Construction material | Extruded aluminum |
| Size options | 41U,42U and 46U (other sizes available) |
| Color options | Dark Gray RAL 7021 |
| Width and depth options | 800x800mm, 800x1000mm. |
| Accessories | Page C.1.8 |

Standard & EU Directives Conformance

- Mechanical structure conforming to EN 61587-1, EN 60297-3-100
- Vibration & shock tests according to MIL-STD 810 E, ETS 300 019
- Corrosion resistance (salt spray) acc. to EN 62208
- IP20 according to DIN EN 60529
- UL test 1244
- NEMA 12 standard
- Equipotential bonding & grounding according to DIN EN 60950-1, IEC 60950-1
- EU Directive 2011/65/EU (RoHS-2)

Mechanical Properties

| | |
|---------------------------|--|
| Static load capacity | 500 kg max. |
| Front door | Single or double glass door |
| Rear door | Single solid metal door |
| Side panels | Detachable, single, fast assembly |
| Profiles | 4 pcs 19" vertical extrusions, sheet steel with mounting holes |
| Cable entries | Top & bottom multiple cable entries |
| Optional cable management | Front and rear vertical cable management Overhead cable management (in row) |
| Mounting | Normal floor or raised floor Optional raised floor and/or ceiling fixing kit Optional floor and/or ceiling shock absorbers |
| Electrical grounding | Internal parts and frame grounding kit |
| Locking options | Standard: Prepared for Cylinder lock Optional: Electronic key-access with managed locking system |

Continued on page C.1.2a

