

AT&T CenterLine

RCE Free Standing Server Cabinets

Description

Free standing 19" server cabinets for IT Rooms and data centers	
Construction material	Extruded aluminum
Size options	41U and 46U (other sizes available)
Color options	Dark Gray RAL 7021
Width and depth options	600x1000mm, 600x1200mm, 800x1000 mm or 800x1200 mm
Accessories	Page C.1.9
Cooling Containment	Suitable for cold and hot corridors



Standard & EU Directives Conformance

- Mechanical structure conforming to EN 61587-1, EN 60297-3-100
- Vibration & shock tests according to MIL-STD 810 E
- Corrosion resistance (salt spray) acc. to EN 62208
- IP20 according to DIN EN 60529
- Equipotential bonding & grounding according to DIN EN 60950-1, IEC 60950-1
- EU Directive 2011/65/EU (RoHS-2)

Mechanical Properties

Static load capacity	500 kg max.
Front door	Detachable, single, 83% perforated
Rear door	Detachable, double, 83% perforated
Side panels	Detachable, single, fast assembly
Profiles	4 pcs 19" server extrusions, sheet steel
Cable entries	Top & bottom multiple cable entries
Optional cable management	Front and rear vertical cable management Overhead cable management (in row)
Mounting	Normal floor or raised floor Optional raised floor and/or ceiling fixing kit Optional floor and/or ceiling shock absorbers
Electrical grounding	Internal parts and frame grounding kit
Locking options	Standard: Prepared for Cylinder lock Optional: Electronic key-access with managed locking system

Continued on page C.1.3a