

AT&T RackLine

Free Standing Server Cabinets

Description

Free standing 19" server cabinets	
Construction material	Sheet Steel
Size options	26U, 42U and 47U (other sizes available)
Width and depth options	600x1000mm or 800x1000mm
Color	Black RAL 9005
Accessories	Page D.5.1

Standard & EU Directives Conformance

- Mechanical structure conforming to EN 61587-1, IEC 60917 & IEC 60297
- Vibration & shock tests according to IEC 60068-2
- Corrosion resistance (salt spray) acc. to ISO 9227, ASTM B117
- IP20 according to IEC 60529
- Bonding & ground continuity according to IEC 61010-1
- EU Directive 2011/65/EU (RoHS-2)

Mechanical Properties

Static load capacity	1000 kg max.
Dynamic load capacity	750 kg max.
Front door	Detachable, single, 82% perforated
Rear door	Detachable, double, 82% perforated
Side panels	Detachable, key-locked
Profiles	U marking on both sides
Mounting	Normal floor or raised floor Optional raised floor fixing kit
Electrical grounding	Internal parts and frame grounding kit
Cabinet row formation	Aligning baying kit
Locking options	Standard: Mechanical lock Optional: Electronic key-access



Ordering Information

Description	Size	Dimensions mm	Color	P/N
Free standing 19" Server Cabinet	26U	600x1000	Black	7116100026A-BK51
Free standing 19" Server Cabinet	42U	600x1000	Black	7116100042A-BK51
Free standing 19" Server Cabinet	47U	600x1000	Black	7116100047A-BK51
Free standing 19" Server Cabinet	42U	800x1000	Black	7118100042A-BK51
Free standing 19" Server Cabinet	47U	800x1000	Black	7118100047A-BK51
Free standing 19" Server Cabinet	26U	600x1000	Gray	7116100026A-GY51
Free standing 19" Server Cabinet	42U	600x1000	Gray	7116100042A-GY51
Free standing 19" Server Cabinet	47U	600x1000	Gray	7116100047A-GY51
Free standing 19" Server Cabinet	42U	800x1000	Gray	7118100042A-GY51
Free standing 19" Server Cabinet	47U	800x1000	Gray	7118100047A-GY51