

## AT&T OutdoorLine

### Outdoor Single Loose-Tube Dielectric Armored Single-Jacket Optical Fiber Cables

#### Description

2-12 fibers outdoor single loose-tube dielectric armored single-jacket FO cables

Fiber type	Select from FiberLine fiber types (Section B.6)
Buffer type	Single PBT jell-filled loose tube
Strength elements & armor	Served swellable glass yarn
Cable jacket material	UV-resistant PE
Fibers color code	TIA-598-C
Jacket color	Black (other colors available)

#### Standard & EU Directives Conformance

- Relevant sections of ANSI/TIA-568.3-D
- Relevant sections of ISO/IEC 11801
- Relevant sections of EN 50173
- EU Directive 2011/65/EU (RoHS-2)

#### Mechanical Properties

Short term bend radius	30xOD mm
Long term bend radius	15xOD mm
Operating temperature	-30 to +70C
Installation temperature	-20 to +70C
Water blocking test	3m cable, 1m water, 24h - IEC 60794-1-2 F5



#### Ordering Information

**FF: Fiber Type**

Description	Cable OD mm	Weight kg/km	Max. Load N		Packaging	P/N
			Short Term	Long Term		
2-Fiber FO Outdoor Dielectric Armored Single Loose-Tube SJ Cable	8.4	60	2000	1000	2000m Drum	24SFFAN002N-BK2N
4-Fiber FO Outdoor Dielectric Armored Single Loose-Tube SJ Cable	8.4	60	2000	1000	2000m Drum	24SFFAN004N-BK2N
6-Fiber FO Outdoor Dielectric Armored Single Loose-Tube SJ Cable	8.4	60	2000	1000	2000m Drum	24SFFAN006N-BK2N
8-Fiber FO Outdoor Dielectric Armored Single Loose-Tube SJ Cable	8.4	60	2000	1000	2000m Drum	24SFFAN008N-BK2N
10-Fiber FO Outdoor Dielectric Armored Single Loose-Tube SJ Cable	8.4	60	2000	1000	2000m Drum	24SFFAN010N-BK2N
12-Fiber FO Outdoor Dielectric Armored Single Loose-Tube SJ Cable	8.4	60	2000	1000	2000m Drum	24SFFAN012N-BK2N