

AT&T FiberLine

Fiber Optic ST/UPC Simplex Multimode Cords

Description

This page shows some of the available combinations of AT&T fiber-optic Simplex Multimode Cords made with multimode fibers and terminated with ST/UPC connectors.

Additional combinations can be selected using the information on page B.3.

Fiber type	Select a multimode fiber from page B.6.
Buffer type	900 μ tight flame retardant LSOH coating
Strength elements	Served aramid and glass yarn
Minicable jacket material	Flame retardant LSOH compound

Standard & EU Directives Conformance

- Relevant sections of ANSI/TIA-568.3-D
- Relevant sections of ISO/IEC 11801
- Relevant sections of EN 50173
- Relevant sections of ANSI/TIA/EIA-604 (FOCIS)
- Relevant sections of IEC 60874
- Relevant sections of IEC 61753
- Relevant sections of IEC 61754
- IEC 60332-1 flame test
- IEC 60754 & IEC 61034
- EU Directive 2011/65/EU (RoHS-2)

Mechanical Properties

Short term bend radius	20xOD mm
Long term bend radius	10xOD mm
Operating temperature	-20 to +60C
Default jacket colors	MM OM1 & OM2: Orange MM OM3: Turquoise MM OM4: Purple



Ordering Information

FF: Fiber Type **CC:** Jacket Color

Description	Length m	Cable OD mm	Packaging	P/N
ST/UPC-ST/UPC Simplex Multimode Cord LSOH	1	3.0	1/Bag - 12/Box	28CFFAA010T-CC61
ST/UPC-ST/UPC Simplex Multimode Cord LSOH	2	3.0	1/Bag - 12/Box	28CFFAA020T-CC61
ST/UPC-ST/UPC Simplex Multimode Cord LSOH	3	3.0	1/Bag - 12/Box	28CFFAA030T-CC61
ST/UPC-ST/UPC Simplex Multimode Cord LSOH	5	3.0	1/Bag - 12/Box	28CFFAA050T-CC61
ST/UPC-ST/UPC Simplex Multimode Cord LSOH	10	3.0	1/Bag - 12/Box	28CFFAA100T-CC61
ST/UPC-FC/UPC Simplex Multimode Cord LSOH	1	3.0	1/Bag - 12/Box	28CFFAE010T-CC61
ST/UPC-FC/UPC Simplex Multimode Cord LSOH	2	3.0	1/Bag - 12/Box	28CFFAE020T-CC61
ST/UPC-FC/UPC Simplex Multimode Cord LSOH	3	3.0	1/Bag - 12/Box	28CFFAE030T-CC61
ST/UPC-FC/UPC Simplex Multimode Cord LSOH	5	3.0	1/Bag - 12/Box	28CFFAE050T-CC61
ST/UPC-FC/UPC Simplex Multimode Cord LSOH	10	3.0	1/Bag - 12/Box	28CFFAE100T-CC61
ST/UPC-LC/UPC Simplex Multimode Cord LSOH	1	2.0	1/Bag - 12/Box	28CFFAP010T-CC61
ST/UPC-LC/UPC Simplex Multimode Cord LSOH	2	2.0	1/Bag - 12/Box	28CFFAP020T-CC61
ST/UPC-LC/UPC Simplex Multimode Cord LSOH	3	2.0	1/Bag - 12/Box	28CFFAP030T-CC61
ST/UPC-LC/UPC Simplex Multimode Cord LSOH	5	2.0	1/Bag - 12/Box	28CFFAP050T-CC61
ST/UPC-LC/UPC Simplex Multimode Cord LSOH	10	2.0	1/Bag - 12/Box	28CFFAP100T-CC61
ST/UPC-LSH/UPC Simplex Multimode Cord LSOH	1	2.0	1/Bag - 12/Box	28CFFAD010T-CC61
ST/UPC-LSH/UPC Simplex Multimode Cord LSOH	2	2.0	1/Bag - 12/Box	28CFFAD020T-CC61
ST/UPC-LSH/UPC Simplex Multimode Cord LSOH	3	2.0	1/Bag - 12/Box	28CFFAD030T-CC61
ST/UPC-LSH/UPC Simplex Multimode Cord LSOH	5	2.0	1/Bag - 12/Box	28CFFAD050T-CC61
ST/UPC-LSH/UPC Simplex Multimode Cord LSOH	10	2.0	1/Bag - 12/Box	28CFFAD100T-CC61

Optional Transmission Properties

Suffix	Connector IL (dB)	Connector RL (dB)
T = Standard Loss connector	0.30 max. 0.20 Typical	20 min.
S = Low-Loss connector	0.15 max. 0.10 Typical	20 min.