

## AT&T CenterLine Fiber Optic Panels

### Standard 19" Fiber Optic Panels

#### Description

1-288 fiber, 2-7U standard 19" fiber optic splicing/distribution panels	
Connector type compatibility - Group A	ST, SC, FC
Connector type compatibility - Group B	LC, MTRJ, LSH (E-2000™)
<b>Splicing with Group A &amp; B connectors</b>	<b>Up to two 36 fiber splicing in each cassette</b>
Distribution with Group A connectors	Up to 24 fiber direct cable termination in each U
<b>Distribution with Group B connectors</b>	<b>Up to 48 fiber direct cable termination in each U</b>
Panel front	Up to 24 removable modules
<b>Panel access</b>	<b>Top and side</b>
Front Cable Management	Tray for patch cord routing and protection

#### Standard & EU Directives Conformance

- Relevant sections of ANSI/TIA/EIA-604 (FOCIS)
- Relevant sections of IEC 60874
- Relevant sections of IEC 61753
- Relevant sections of IEC 61754
- Plastic parts: UL94 V-0 flame test
- EU Directive 2011/65/EU (RoHS-2)

#### Mechanical Properties and Features

Frame	Steel, colored black
Front cover	Hinged transparent cover
Operating temperature	-10 to +60C at 5-85% RH (non condensing)
Storage temperature	-40 to +70C
Plastic parts	High-impact flame retardant materials
Port identification	Numbers and designated space printed on the cover
Panel identification	Designated space at the panel front

#### Ordering Information - Panels

Description	Units	Fiber Capacity		Cassette Capacity	Module Capacity	Size mm	Packaging	P/N
		A	B					
Standard 2U Blank 19" Fiber Optic Panel	2U	36	72	2	6	83x483x356	1/Box	27S00NV072A-MT2U
Standard 3U Blank 19" Fiber Optic Panel	3U	72	144	4	12	132x483x356	1/Box	27S00NV144A-MT3U
Standard 7U Blank 19" Fiber Optic Panel	7U	144	288	8	24	293x483x356	1/Box	27S00NV288A-MT7U

Continued on page C.4.3.1a

