

### AT&T CablingGuard

#### Smart Card

##### Description

Smart Card for CablingGuard Smart Ready Panels	
Smart Ready Panel Compatibility	Cat5e, Cat6 or Cat6A Pre-terminated FO Patch Panels Standard FO Patch Panels
Connectivity	RJ45 Jack 52-pins Edge Connector
Color	Red.

##### Standard & EU Directives Conformance

- FCC Subpart F 68.5 Compliant

##### Approvals & Pending Approvals

- UL 1863
- CSA 22.2

##### Mechanical Properties

Material	Red or Yellow Cover is made of plastic (non metal)
Thickness	1.52 mm
Power Requirements	Connection to CablingGuard Infrastructure Analyzer
Operating Life	Minimum 50 insertions
Contact Plating	1.25µm Gold
<b>Temperature Rating</b>	
Installation	0 to 50°C, 15-90% RH (non-condensing)
Operation	0 to 50°C, 15-90% RH (non-condensing)
Storage	-10 to 60°C, 10-95% RH (non-condensing)



##### Ordering Information - Smart Card

Description	Size	Dimensions mm	Color	P/N
CablingGuard CL2 Smart Card for Smart Ready Copper Patch Panel	1U	42x62x22	Red	CRSCPCL201N
CablingGuard FL2 Smart Card for Smart Ready FO Patch Panels	1U	42x62x22	Yellow	CRSFPFL201N